



**ECOCARE SERVICES LLP**  
My SingPost Box 880171  
Singapore 919191  
Tel/Fax: 65 63103163  
Mobile: 65 96857026  
Email:ecocare\_services@yahoo.com.sg  
UEN No:T07LL0059J  
GST Reg No:M90357607P

## Ecomax

**DESCRIPTIONS:** **Ecomax** is a heavy duty industrial surface renovator that breaks up the molecular structures of dirt, sludge, exhaust stains, grease, ink, grime and floats them away from the surfaces without much agitation and danger of solvents.

**APPLICATIONS:** **Ecomax** is widely used in deck washing industry, truck washing operators, manufacturing industrial plants, marine vessels, oil rigs, engine rooms, printing industries, schools, building complexes, automotive workshops, aircraft hangers, truck terminals etc.

### ADVANTAGES:

- **POWERFUL AND HIGHLY EFFECTIVE**  
**Ecomax** has a superior renovating power that breaks down dirt, sludge and grime that bond to surfaces and floats them away.
- **NON-FLAMMABLE**  
**Ecomax** is non-flammable and will not support combustion at any temperature.
- **MULTI-PURPOSE**  
It renovates on concrete, plastic, metal, rubber and most water surfaces safely with maximum effectiveness. **Ecomax** penetrates, emulsifies and suspends greasy soils, carbon stains, fish and animal oils suitable for tanks cleaning applications.
- **ECONOMICAL**  
**Ecomax** saves costly labour time and can be diluted up to 100 parts of water for light application.
- **BIODEGRADABLE**  
It is completely biodegradable, environmentally safe and will not contribute to water pollution.
- **SAFE TO USE**  
**Ecomax** does not emit harmful fumes and thus safe to use.

### DIRECTIONS:

**Ecomax** can be used as concentrated or diluted. It is used by normal method of cleaning – brush, mop, spray, recirculation, direct injection and is also very effective in steam and hot tank cleaning.

For general cleaning, it can be diluted 1 part of **Ecomax** to 100 parts of water depending on how sever the soil or grease. Mop, brush or wipe method is acceptable.

For heavy soil or grease, dilute 1 part of **Ecomax** with 5 parts of water. Let soak for 20 to 50 secs before washing solution away with water. Slight agitation may be necessary for heavy soil.

For engine block and hot tank cleaning, dilute 1 part of **Ecomax** to 5 parts of water.

### PROPERTIES:

Type : Alkaline aqueous grease solvent.  
Appearance : Clear water-based solution.  
Odor : Light, non-fuming.  
pH : 13-14.  
Flammability : Non-flammable.  
Active Ingredient : Biodegradable penetrants and emulsifiers, inorganic compounds with low foaming surfactants.