



ECOCARE SERVICES LLP
My Mail Box 880171
Singapore 919191
Tel/Fax: 65 63103163
Mobile: 65 96857026
Email:ecocare_services@yahoo.com.sg
UEN No:T07LL0059J
GST Reg No:M90357607P

Safety Solvent Degreaser

DESCRIPTIONS: **Safety Solvent Degreaser** is a safe and fast drying solvent cleaner specially designed for removing impurities such as oils, grease, dirt, carbon particles etc, from most electrical equipments.

APPLICATIONS: **Safety Solvent Degreaser** can be used for power tools, electrical motors, generators, printing equipment, elevator, marine and industrial equipment, switch gear, panel and belt converters etc.

ADVANTAGES:

- **NON CORROSIVE**
Safety Solvent Degreaser replaces other solvents such as trichloroethylene and other toxic or highly flammable solvents. It is non conductive and non corrosive.
- **NON-FLAMMABLE**
It is non-flammable and has no flash point at all.
- **LEAVE NO RESIDUE**
Safety Solvent Degreaser evaporates fast and does not leave any residue on sensitive parts and equipments.
- **SAVE TIME & MONEY**
Machinery does not have to shut down during cleaning thus cutting down costly hours of operation downtime. **Safety Solvent Degreaser** degreases electrical motor or equipments; helps prolong life span and improve equipments' power efficient.
- **SAFE TO USE**
Safety Solvent Degreaser is safe to human skin and does not emit harmful fumes.

Instructions:

Safety Solvent Degreaser can be used while equipment is running, but adequate precautions and ample ventilation should be provided. Use this cleaner neat by spray, soak tank, brush or vapour degreasing. Apply cleaner on parts that need to be cleaned and allow chemical to penetrate for 5-10 minutes for dipping purposes. Use air-pressure gun to blow off solid impurities and hasten drying. There is a possibility that it may affect some types of rubber or plastics from the component. Thus it is recommended to test on a small area for any reaction before cleaning.

Properties:

Type : Fast drying solvent degreaser.
Flammability : Non Flammable. No flash point.
Toxicity : Low. TLV 100 ppm.
Composition : Combination of carefully selected chlorinated and none chlorinated solvents.